



- 17W Main switch only duplex consumer unit
- Includes a 100A main switch with twin line and neutral supply terminals and 100A flexible busbar assemblies
- Accepts all Wylex miniature final circuit protection devices; MCBs, RCBOs and AFDDs
- Accepts the Wylex miniature type 2 SPD NMT2SPD3W/1
- Constructed from a full metal enclosure with a temporary locking facility when installed in conjunction with the Wylex locking bar NMDLBK

Product Specification Data	Revision Date: 11/11/2022
Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	1
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	506 mm
Width	241 mm
Width in number of modular spacings	10
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	No
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Main switch only
Total final circuit modular ways	17
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	17

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Colour RAL

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited,** Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk