

Ei450



RadioLINK Alarm Controller



- Install as part of the system to get more control over your alarms
- Test, Locate and Silence functions
- RadioLINK+ Wireless interconnection
- 10 year Lithium battery powered
- LEDs for a visual display of Fire or Carbon Monoxide alarm activation



Description

The Ei450 RadioLINK Alarm Controller is used to control all wirelessly interconnected fire and CO alarms from one location. It allows the user to remotely Test, Locate and Silence alarms in the system and is powered by a built-in 10 year lithium cell

Technical

RF Frequency (MHz)	868.499	RF Range (m)	>100 in free air
Indicators	Red - Fire, CO / Yellow - EoL	Battery Type	Lithium primary
Technologies	RadioLINK		

Dimensions & Weights

Depth (mm)	27	Height (mm)	90
Width (mm)	90	Product weight (kg)	0.112
Packaged weight (kg)	0.178		

Approvals & Warranty

Certification/Approvals	EN 300-220-2 / EN 301 489-1, EN 301 489-3 / EN 60065	Warranty	5 year warranty
EAN Number	5099383004731		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------

T 01691 664100 E enquiries@aico.co.uk W www.aico.co.uk

Company Registration No.: 2544399
Producer Registration No.: BPRN00307

WEEE Registration No.: WEE/AE0109WY Battery

an  Company